IN THE CLAIMS

1. (currently amended) A <u>processor implemented</u> method of forming distribution content that includes a data module, the data module including a script, said method comprising:

scanning the script to detect a plurality of character strings that each match predetermined criteria;

sorting the plurality of character strings in order of their appearance frequency in the script;

associating, for each one of the plurality of character strings, that character string with a specific one of a plurality of substitute characters or character strings;

searching the script for a given one of the plurality of character strings; and

replacing the given one of the plurality of character strings with a the specific one of the plurality of substitute characters or character strings that is associated with the given one of the plurality of character strings, the specific one of the plurality of substitute characters or character strings having fewer characters than the given one of the plurality of character strings.

2. (currently amended) A <u>processor implemented</u> method according to claim 1, further comprising:

temporarily storing the distribution content after carrying out said replacing step, and then distributing the content.

- 3. (currently amended) A <u>processor implemented</u> method according to claim 1, wherein the given <u>one of the plurality of character strings</u> is a function name or a variable name.
- 4. (currently amended) A <u>processor implemented</u> method according to claim 261, further comprising:

Application No.: 09/786,878

determining whether the specific one of the plurality of substitute characters or character strings is a system reserved word, and when the specific one of the plurality of substitute characters or character strings is a system reserved word, replacing the specific one of the plurality of substitute characters or character strings with a further one of the plurality of substitute characters or character strings with a further one of the plurality of substitute characters or character strings prior to carrying out said associating step.

5. (currently amended) A <u>processor implemented</u> method according to claim 1, further comprising:

searching the script for a further one of the plurality of character strings that does not affect execution of the script; and deleting the further one of the plurality of character strings from the script.

- 6. (currently amended) A <u>processor implemented</u> method according to claim 5, wherein the further <u>one of the plurality of character strings</u> is a comment string preceded by a predetermined delimiter.
- method according to claim 261, wherein said determining step includes scanning the script to detect a plurality of character strings that each match the predetermined criteria, said method further comprising: sorting the plurality of character strings in order of their appearance frequency in the script, andsaid associating step including, for each one of the plurality of character strings, associating that character string with a specific one of a plurality of substitute characters or character strings, whereby when a the given one of the plurality of character strings has a greater appearance frequency than another one of the plurality of character strings, the specific one of the plurality of substitute characters or character strings that is associated with the given one of the plurality

of character strings has a same or smaller number of characters than the <u>specific one of the plurality of</u> substitute characters or character strings that is associated with the another one of the plurality of character strings.

8. (currently amended) A <u>processor implemented</u> method of distributing content that includes a plurality of data modules, at least one of the plurality of modules including a script, said method comprising:

scanning the script of the at least one data module to detect a plurality of character strings that each match predetermined criteria;

sorting the plurality of character strings in order of their appearance frequency in the script;

associating, for each one of the plurality of character strings, that character string with a specific one of a plurality of substitute characters or character strings;

searching the script of the <u>at least one</u> data module for a given <u>one of the plurality of</u> character strings;

replacing the given one of the plurality of character strings with a the specific one of the plurality of substitute characters or character strings that is associated with the given one of the plurality of character strings, the specific one of the plurality of substitute characters or character strings having fewer characters than the given one of the plurality of character strings;

storing the <u>at least one</u> data module after carrying out said replacing step; and

distributing the stored data module.

9. (currently amended) A <u>processor implemented</u> method according to claim 8, wherein the given <u>one of the</u>

plurality of character strings is a function name or a variable name.

10. (currently amended) A <u>processor implemented</u> method according to claim 288, further comprising:

determining whether the specific one of the plurality of substitute characters or character strings is a system reserved word, and when the specific one of the plurality of substitute characters or character strings is a system reserved word, replacing the specific one of the plurality of substitute characters or character strings with a further one of the plurality of substitute characters or character strings with a further one of the plurality of substitute characters or character strings prior to carrying out said associating step.

11. (currently amended) A <u>processor implemented</u> method according to claim 8, further comprising:

searching the script for a further <u>one of the plurality of character strings</u> that does not affect execution of the script; and deleting the further <u>one of the plurality of character strings</u> from the script.

- method according to claim 11, wherein the further one of the plurality of character strings is a comment string preceded by a predetermined delimiter.
- method according to claim 288, wherein said determining step includes scanning the script to detect a plurality of character strings that each match the predetermined criteria, said method further comprising: sorting the plurality of character strings in order of their appearance frequency in the script, andsaid associating step including, for each one of the plurality of character strings with a specific one of a plurality of substitute characters or character strings, whereby when a the given one of the plurality

of character strings has a greater appearance frequency than another one of the plurality of character strings, the <u>specific one of the plurality of substitute characters</u> or character strings that is associated with the given one of the plurality of character strings has a same or smaller number of characters than the <u>specific one of the plurality of substitute characters</u> or character strings that is associated with the another one of the plurality of character strings.

14. (currently amended) An apparatus for distributing content that includes a plurality of data modules, at least one of the plurality of modules including a script, said apparatus comprising:

means for scanning the script to detect a
plurality of character strings that each match
predetermined criteria;

means for sorting the plurality of character strings in order of their appearance frequency in the script;

means for associating, for each one of the plurality of character strings, that character string with a specific one of a plurality of substitute characters or character strings;

means for searching the script of the <u>at least</u> one data module for a given one of the plurality of character strings;

means for replacing the given one of the plurality of character strings with a the specific one of the plurality of substitute characters or character strings that is associated with the given one of the plurality of character strings, the specific one of the plurality of substitute characters or character strings having fewer characters than the given one of the plurality of character strings;

means for storing the <u>at least one</u> data module after replacing the given <u>one of the plurality of character strings</u> with the <u>specific one of the plurality of substitute characters or character strings; and</u>

means for distributing the stored data module.

- 15. (currently amended) An apparatus according to claim 14, wherein the given one of the plurality of character strings is a function name or a variable name.
- 16. (currently amended) An apparatus according to claim 3014, further comprising:

means for determining whether the specific one of the plurality of substitute characters or character strings is a system reserved word, and when the specific one of the plurality of substitute characters or character strings is a system reserved word, for replacing the specific one of the plurality of substitute characters or character strings with a further one of the plurality of substitute characters or character strings with the given one of the plurality of character strings.

17. (currently amended) An apparatus according to claim 14, further comprising:

means for searching the script for a further one of the plurality of character strings that does not affect execution of the script; and

means for deleting the further <u>one of the</u> plurality of character strings from the script.

- 18. (currently amended) An apparatus according to claim 17, wherein the further one of the plurality of character strings is a comment string preceded by a predetermined delimiter.
- 19. (currently amended) An apparatus according to claim $\frac{30}{14}$, wherein $\frac{14}{14}$ wherein $\frac{14}{14}$ wherein $\frac{14}{14}$ includes $\frac{14}{14}$ wherein $\frac{14}{14}$ includes $\frac{14}{14}$ includ

strings that each match the predetermined criteria, said apparatus further comprising: means for sorting the plurality of character strings in order of their appearance frequency in the script, andsaid means for associating including, for each one of the plurality of character strings, means for associating that character string with a specific one of a plurality of substitute characters or character strings, whereby when a the given one of the plurality of character strings has a greater appearance frequency than another one of the plurality of specific one of the plurality of character strings, the substitute characters or character strings that is associated with the given one of the plurality of character strings has a same or smaller number of characters than the specific one of the plurality of substitute characters or character strings that is associated with the another one of the plurality of character strings.

20. (currently amended) A <u>processor implemented</u> method of reducing the size of source code, said method comprising:

scanning the source code to detect a plurality of character strings that each match predetermined criteria;

sorting the plurality of character strings in order of their appearance frequency in the source code;

associating, for each one of the plurality of character strings, that character string with a specific one of a plurality of substitute characters or character strings;

searching the source code for a given one of the plurality of character strings; and

replacing the given one of the plurality of character strings with a the specific one of the plurality of substitute characters or character strings that is associated with the given one of the plurality of character

strings, the <u>specific one of the plurality of substitute</u> characters or character strings having fewer characters than the given one of the plurality of character strings.

- 21. (currently amended) A <u>processor implemented</u> method according to claim 20, wherein the given <u>one of the plurality of character strings</u> is a function name or a variable name.
- 22. (currently amended) A <u>processor implemented</u> method according to claim <u>3220</u>, further comprising:

determining whether the specific one of the plurality of substitute characters or character strings is a system reserved word, and when the specific one of the plurality of substitute characters or character strings is a system reserved word, replacing the specific one of the plurality of substitute characters or character strings with a further one of the plurality of substitute characters or character strings with a further one of the plurality of substitute characters or character strings prior to carrying out said associating step.

23. (currently amended) A <u>processor implemented</u> method according to claim 20, further comprising:

searching the source code for a further <u>one of</u>
the plurality of character strings that does not affect
execution of the source code; and

deleting the further one of the plurality of character strings.

- 24. (currently amended) A <u>processor implemented</u> method according to claim 23, wherein the further <u>one of the plurality of character strings</u> is a comment string preceded by a predetermined delimiter.
- 25. (currently amended) A <u>processor implemented</u> method according to claim 3220, wherein said determining step includes scanning the source code to detect a plurality of character strings that each match the predetermined criteria,

said method further comprising: sorting the plurality of character strings in order of their appearance frequency in the source code, andsaid associating step including, for each one of the plurality of character strings, associating that character string with a specific one of a plurality of substitute characters or character strings, whereby when a—the given one of the plurality of character strings has a greater appearance frequency than another one of the plurality of character strings, the specific one of the plurality of substitute characters or character strings that is associated with the given one of the plurality of character strings has a same or smaller number of characters than the specific one of the plurality of substitute characters than the specific one of the plurality of character strings.

- 26. (cancelled)
- 27. (currently amended) A <u>processor implemented</u> method according to claim 261, further comprising:

storing the given one of the plurality of character strings and the specific one of the plurality of substitute characters or character strings associated with the given one of the plurality of character strings in a correspondence table.

- 28. (cancelled)
- 29. (currently amended) A <u>processor implemented</u> method according to claim 288, further comprising:

storing the given <u>one of the plurality of character</u> strings and the <u>specific one of the plurality of substitute</u> characters or character strings <u>associated with the given one of the plurality of character strings</u> in a correspondence table.

- 30. (cancelled)
- 31. (currently amended) An apparatus according to claim 3014, further comprising:

means for storing the given one of the plurality of character strings and the specific one of the plurality of substitute characters or character strings associated with the given one of the plurality of character strings in a correspondence table.

- 32. (cancelled)
- 33. (currently amended) A <u>processor implemented</u> method according to claim 3220, further comprising:

storing the given one of the plurality of character strings and the specific one of the plurality of substitute characters or character strings associated with the given one of the plurality of character strings in a correspondence table.